

CIG-BTY

Battery Powered Wall Mounted Ciglow Flameless Lighter with Control Timer

Description

The lighter has been designed for areas that cannot be powered by mains electricity. The unit is available in two sizes to house either one or two 12 volt batteries. The unit is a weatherproof polycarbonate enclosure and is fitted with an illuminated push button and allows access to the workings of the lighter through a removable faceplate thus leaving the back box permanently secured to the wall.

Mounting Style

This lighter is mounted onto a wall or similar flat surface. The unit is powered by a 12v battery which can be charged by a Ciglow solar cell (CIG-SOL), wind turbine or similar power source.

Weatherproof Rating

This lighter is rated IP65 and is suitable for outdoor use in all weather conditions.

Element

This lighter uses the CIG-SL internally mounted screw-in element.

Operation

This lighter operates a safety control timer. The user presses the push button then releases. The unit then runs through a cycle which heats up the element, switches it off, and then adds in a cool down period. The timer cannot be restarted whilst this cycle is running.

Dimensions

Single battery box: 250 mm (h) x 180 mm (w) x 100 mm (d)

Twin battery box: 300 mm (h) x 200 mm (w) x 160 mm (d)

Weight

4 kg (including battery)



207 Cotton Exchange, Bixteth Street
Liverpool, L3 9LQ, United Kingdom
info@ciglow.co.uk
Tel: +44(0) 151 709 8800

